



# Video

## RAM Wireless 3X PTZ Camera

Rugged and Miniature

### Wireless Miniature 3X PTZ Camera

- **Digital 3X Digital Zoom and Digital Tilt**
- **Rugged Weatherproof Housing**
  - **Temperature range -30° F to 140° F**
  - **No image degradation due to humidity build up or deterioration of acrylic dome**
  - **100% sealed; fully submersible**

**2" Diameter**



**360° Rotation**

#### Specifications

Image Sensor	1/3" High Resolution SONY SUPER HAD CCD
Total pixels	NTSC 811(H) X 508(V) PAL 795(H) X 596(V)
Effective pixels	NTSC 768(H) X 492(V) PAL 752(H) X 582(V)
Horizontal Resolution	520 TV Lines
Electronic shutter	NTSC 1/60-1/100,000(sec) automatic , PAL 1/50-1/100,000(sec) automatic
S/N Ratio	More Than 50dB(AGC OFF)
Sensitivity	1.5Lux @ F2.0 (30 IRE, AGC MAX, DAY & NIGHT ON))
Sync System	Internal
Gamma Correction	$\gamma=0.45$
Video Output	1 [Vp-p] Composite 75Ω unbalanced
Current consumption	A/D Key type : 150mA or Less, RS-485 type : 180mA or Less
Input Power Source	DC12V (±10%)
Operating Temperature	-10°C ~ +50°C
Board Lens	f3.6mm(Standard)
PinholeLens	Cone Pinhole f3.7mm(Standard) / Super Cone Pinhole f4.3mm(Standard)
Varifocal Lens	Varifocal f4.0~8.0mm
Remote Control	A/D Key(Bright, DAY & NIGHT ON/OFF)
Functions Option	RS-485 Cable, 3X Zoom(Max)
Dimension	38mm(H) 38mm(V)

EOI, Inc.  
412 Halsey Road  
Annapolis, MD 21401

For more information, please contact us.

Phone: 443-482-9464

Email: [eoi-inc@eoi-inc.com](mailto:eoi-inc@eoi-inc.com)

Web: [www.eoi-inc.com](http://www.eoi-inc.com)

